

Antenna cable - RAD-PIG-EF316-N-N - 2867704

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Adapter cable, 50 cm pigtail, N (male) -> N (female), 50 Ω impedance



Product Features

- As an adapter between devices and cables
-

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	68.4 GRM
Custom tariff number	85442000
Country of origin	Poland

Technical data

Dimensions

Fixed cable length	50 cm
External diameter	2.50 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

General

Connection 1	Connector connection
Connection method	N (female)
Connection 2	Connector connection
Connection method	N (male)
Cable type	EF 316
Outer sheath, material	RADOX [®] (LSFH)
Minimum bending radius	12.50 mm
Frequency range	900 MHz

Antenna cable - RAD-PIG-EF316-N-N - 2867704

Technical data

General

	2.4 GHz
	5 GHz
Impedance	50 Ω

Attenuation

868 / 900 MHz	0.6 dB
2.4 GHz	1 dB
5 GHz	1.4 dB

Classifications

eCl@ss

eCl@ss 4.0	27060805
eCl@ss 4.1	27060805
eCl@ss 5.0	27061805
eCl@ss 5.1	27061805
eCl@ss 6.0	27061805
eCl@ss 7.0	27061805

ETIM

ETIM 2.0	EC000019
ETIM 3.0	EC000019
ETIM 4.0	EC000019
ETIM 5.0	EC000019

UNSPSC

UNSPSC 6.01	26121608
UNSPSC 7.0901	26121608
UNSPSC 11	26121608
UNSPSC 12.01	26121608
UNSPSC 13.2	26121608

Approvals

Approvals

Approvals

EAC / EAC

Antenna cable - RAD-PIG-EF316-N-N - 2867704

Approvals

Ex Approvals

Approvals submitted

Approval details

EAC

EAC
