T D	т п	D	C B	A		
Three to be a constrained of the second seco	ØF				4	
ω 			LAYOUT SHOWN AS EXAMPLE		3	
	Keying Shown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	F25.4 MaxZ31.5 MaxVV THREADM22x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer ► -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed	2	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D115W15AB			
-Temperature Range _: -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	MOD CUSTOMER DRAWING	N°	
		TITLE	Aluminium Inline	e plug 8D series		
BASIC SERIES: 8D 1 - 15 W SHELL TYPE : In line Receptacle	15 A B	SCALE - NA	General linear Tolerances:	NPRDS / PROJECT 859	1	
CONTACT TYPE : Standard Crimp Contact				This document is the property of SOURIAU it must not be reproduced or		
PLATING : W = Olive drab Cadmium	CONTACT TYPE : PIN(3001		SOURIAU DRG			
H G	F E		8D115W15AB	B-C 1/2		

	T G	н т	т	D	0	B		_
	Contact Layout							
4	$\begin{array}{c} & & & & \\ & & & \\ & & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & \\ & & \\ &$							4
	Contacts (Insert arrangement 15-15) Contact position ID Location X-axis Contact position ID Location A +.100 (2.54) +.225 (5.72) J 244 (6.20) +.014 (0.36) B +.202 (5.13) +.140 (3.56) K 220 (5.13) +.140 (3.56) C +.244 (6.20) +.014 (0.36) L 100 (2.54) +.225 (5.72) D +.218 (5.54) 113 (2.87) M +.000 (.00) +.140 (3.56) E +.126 (3.20) 209 (5.31) N +.110 (.279) +.040 (.102) F +.000 (.00) 244 (6.22) P +.000 (.00) 077 (1.96) G 126 (3.20) 209 (5.31) R 110 (.279) +.040 (1.92) H 218 (5.54) 113 (2.87)							_
ω	Shelli Arrangement no. Number of contacts Size contacts Service rating Contact location Supersedes 15 -15 1 16 P MS20052-15	-						3
					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
2					CountryJurisdiction & Control ListFRNot Listed			2
					PN: 8D115W15AB			
				A 27-09-2016	5 First Release			_
				ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
				TITLE	TITLE Aluminium Inline plug 8D series			
				SCALE	General linear Tolerances:	NPRDS / PROJECT 859		-
_				SOURIAU	WWW.SOURIAU.CO	This document is the pro	ced or	1
				FORMAT A3	SOURIAU E	DRG N°	SHEET	
l	H G	F	E		8D115W1	B A		