


MATERIALS:

INSULATOR: THERMOPLASTIC POLYESTER, UL94V-0
CHEMICAL RESISTANCE, COLOR BLACK
SHEET: STEEL, NICKEL PLATED
CONTACT: BRASS

GOLD FLASH (CONTACT CODE 264)
15 MICROINCHES GOLD (CONTACT CODE 364)
30 MICROINCHES GOLD (CONTACT CODE 664)
TIN PLATING ON TAIL ENDS

ELECTRICAL:

CURRENT RATING: 5 AMPERES
DW: 1000VAC rms AT SEA LEVEL
INSULATION RESISTANCE: 5000 MEGOHMS MIN.
CONTACT RESISTANCE: 10 MILLIOHMS MAX.
WORKING TEMPERATURE: -55° TO +125° C



THIS SERIES FULLY CONFORMS TO THE
EUROPEAN UNION DIRECTIVES 2002/95/EC
AND 2002/96/EC FOR ROHS COMPLIANCY.

ORDERING CODE

SERIES _____

NUMBER OF CONTACTS _____

CONTACT FINISH CODE _____

GROUNDING FEATURE _____

1- .120(3.05) DIA. THROUGH HOLE

3- TWO PRONG BOARDLOCKS FOR .120(3.05)DIA.HOLE

5- 4-40 UNC THREADED MOUNTING HOLE

7- REAR ONLY TWO-PRONG BOARDLOCKS

MOUNTING OPTIONAL _____

2- 4-40 UNC THREADED INSERT

3- 4-40 UNC HEX THREADED STANDOFF

4- .125(3.18) DIA. THROUGH HOLE

661-025-364-033

| NUMBER OF CONTACTS | "A" Inch (mm) | "B" Inch (mm) | "C" Inch (mm) | "E" Inch (mm) | "F" Inch (mm) |
|--------------------|------------------|------------------|------------------|------------------|------------------|
| 9 | 1.214 (30.84) | .984 (24.99) | .667 (16.92) | .432 (10.97) | .108 (2.74) |
| 15 | 1.545 (39.24) | 1.312 (33.32) | .994 (25.25) | .756 (19.20) | .108 (2.74) |
| 25 | 2.088 (53.04) | 1.852 (47.04) | 1.534 (38.96) | 1.304 (33.12) | .109 (2.76) |
| 37 | 2.730 (69.34) | 2.500 (63.50) | 2.182 (55.42) | 1.956 (49.68) | .109 (2.76) |

661 SERIES SUBMINIATURE D CONNECTOR PLUG(PIN)/PLUG(PIN)
.625(15.88) CENTER/CENTER DUAL PORT RIGHT ANGLE

DRAWN: F.BRIONES DATE: NOV. 26/97
CHECKED: DATE:

PART NUMBER
SEE ORDERING CODE

DRAWING NUMBER
661-000-001

ISSUE
3

EDAC INC
TORONTO, ONTARIO
CANADA

YOUR CONNECTION TO QUALITY & SERVICE

SALES/661000