

## Specification Sheet

Part Number: 151-01631



VHB Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66HIRHSUV/Acrylic, Black, 100/pkg

**Article Number**

151-01631

**Type**

MB4A

**Color**

Black (BK)

**Features & Benefits**

- For use with 18 through 50 pound HellermannTyton cable ties.
- Extremely durable adhesive achieves high pull-off force and is unaffected by vibration.
- Multiple sizes accommodate a range of cable ties.
- 4-way opening allows cable ties to be installed parallel or perpendicular to wire bundles.
- Predrilled holes extend mounting options and security.
- Mount made of proprietary, impact-modified PA66 material for extraordinary durability, and is heat stabilized and UV resistant for extended life outdoors.
- Peel and stick for quick, convenient use in extreme-duty applications.

**Quantity Per**

bag

**Product Description**

HellermannTyton offers adhesive mounts in a variety of sizes to match your cable tie size and extreme-duty application needs. The mount features 3M™ VHB™ (Very High Bond) adhesive, which actually builds strength over time and holds securely to difficult materials such as aluminum, steel, plastics and painted and powder-coated surfaces.

**Short Description**

VHB Adhesive Base, 1.12" x 1.12", .18" Max Tie Width, .18" Hole Dia, PA66HIRHSUV/Acrylic, Black, 100/pkg

**Global Part Name**

MB4A-PA66HIRHSUV-BK

**Length L (Imperial)**

1.12

**Length L (Metric)**

28.5

**Fixation Method**

Adhesive

**Width W (Imperial)**

1.12

**Width W (Metric)**

28.5

**Cable Ties**

T18 - T50

**Height H (Imperial)**

.22

**Height H (Metric)**

5.60

**Cable Tie Width Max (Imperial)**

0.18

**Cable Tie Width Max (Metric)**

4.6

**Mounting Hole Diameter D (Imperial)**

0.18

**Mounting Hole Diameter D (Metric)**

4.6 mm

**Mounting Hole Diameter D Min (Imperial)** 0.18

**Mounting Hole Diameter D Max (Imperial)** 0.18

**Mounting Hole Diameter D Max (Metric)** 4.6

**Mounting Hole Centers (Imperial)** 0.8

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Adhesive** Acrylic foam

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +176°F (-40°C to +80°C)

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

