

Specification Sheet

Part Number: CTAM110C2



Cable Tie Anchor Mount, 0.17" Hole Dia., 0.2" Max Tie Width, PA66, White, 100/pkg

Article Number	151-31103
Type	CTAM1
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Suitable for applications with minimal space.•CTAM has 4-way entry design for use in line or at 90° angle to cable run.•CTAM mounts are available in different sizes and materials.
Quantity Per	bag
Product Description	Anchor Mounts for cable ties are suitable for applications with minimal space. Anchors are mounted onto the equipment prior to cable installation and take up no more space than the cable itself. Choose between a four-way entry design that can be used either 'in line' or at 90 degrees to the cable run.
Short Description	Cable Tie Anchor Mount, 0.17" Hole Dia., 0.2" Max Tie Width, PA66, White, 100/pkg

Global Part Name

CTAM1-PA66-WH

Length L (Imperial)

0.8

Length L (Metric)

20.4

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

0.4

Width W (Metric)

10.2

Cable Ties

T18 - T50

Height H (Imperial)

0.2

Height H (Metric)

5.1

Cable Tie Width Max (Imperial)

0.2

Cable Tie Width Max (Metric)

5.0

Mounting Hole Diameter D (Imperial)

0.17

Mounting Hole Diameter D (Metric)

4.3 mm

Mounting Hole Diameter D Max (Metric)

4.3

Material

Polyamide 6.6 (PA66)

Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL ANSI/UL 1565 UL ANSI/UL 746B UL ANSI/UL 62275
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Metric)	2